



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
[www.uspto.gov](http://www.uspto.gov)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/666,079	09/19/2003	Brent O'Meagher	TRMB1400	8440
7590	08/10/2005		EXAMINER	
WAGNER, MURABITO & HAO LLP			SHEDRICK, CHARLES TERRELL	
Third Floor			ART UNIT	PAPER NUMBER
Two North Market Street				
San Jose, CA 95113			2687	

DATE MAILED: 08/10/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

<b>Office Action Summary</b>	<b>Application No.</b>	<b>Applicant(s)</b>
	10/666,079	O'MEAGHER, BRENT
Examiner	Art Unit	
Charles Shedrick	2687	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

## Status

1)  Responsive to communication(s) filed on 19 September 2003.

2a)  This action is **FINAL**.                            2b)  This action is non-final.

3)  Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

## Disposition of Claims

4)  Claim(s) 1-30 is/are pending in the application.  
4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.  
5)  Claim(s) \_\_\_\_\_ is/are allowed.  
6)  Claim(s) 1-30 is/are rejected.  
7)  Claim(s) \_\_\_\_\_ is/are objected to.  
8)  Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

## Application Papers

9)  The specification is objected to by the Examiner.

10)  The drawing(s) filed on 9/19/03 is/are: a)  accepted or b)  objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)  The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

12)  Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).  
a)  All    b)  Some \* c)  None of:  
1.  Certified copies of the priority documents have been received.  
2.  Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.  
3.  Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

1)  Notice of References Cited (PTO-892)  
2)  Notice of Draftsperson's Patent Drawing Review (PTO-948)  
3)  Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)  
Paper No(s)/Mail Date \_\_\_\_\_.  
4)  Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_.  
5)  Notice of Informal Patent Application (PTO-152)  
6)  Other: \_\_\_\_\_.  
\_\_\_\_\_

## DETAILED ACTION

### *Claim Rejections - 35 USC § 102*

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1-8, 10-18, 20-28, and 30 are rejected under 35 U.S.C. 102(e) as being anticipated by Robbins (U.S. Patent Pub #2002/0198657 A1).

Consider **claim 1** Robbins clearly show and disclose a method for delivering Virtual Reference Station data (VRS) data derived by a VRS network processor **105 subsystem** (**figure 1**) at a VRS control station **105** (**figure 1**) for a designated location to a mobile position determination unit **115** (**figure 1**) with a terrestrial communication link, said method comprising: creating a data message comprising pseudorange data derived for said designated location and pseudorange correction for a designated region surrounding said designated location (**paragraph 0054**); sending said data message via a cellular telephone connection between said VRS control station and a base station located in the designated region surrounding said designated location to a mobile position determination unit using a radio transmitter(**paragraphs 0058 and 0064**)(i.e., the distribution system 110 of figure 1 can comprise of delivery media to GSM telephones. GSM networks are well known in the art to consist of base stations, transmitters, etc. Based on the transmission mediums that are inherent in a GSM network the above stated transmitting can be accomplished).

Consider **claim 2**, and as applied to claim 1 above, Robbins clearly show and disclose a method wherein said VRS control center receives a request for said Virtual Reference Station data and further comprising: deriving the pseudorange data and pseudorange corrections in response to said request (i.e. The declared location of a mobile unit)(**paragraph 0060**).

Consider **claim 3**, and as applied to claim 2 above, Robbins discloses a method wherein receiving said request from said base station (i.e. using a GSM mobile network as the distribution system it is clear that the request must traverse or originate in some way, shape or form involving a base station. The basic functionality of a BTS is to receive and transmit)(**paragraph 0058 and 0064**).

Consider **claim 4**, and as applied to claim 3 above, Robbins discloses the method of initiating said request in response to receiving a message (i.e.,varying message types )(**paragraph 0094 and 0095**) from said mobile position determination unit receiving said request from said mobile position determination unit **115 (figure 1)** (i.e., an integrated GSM phone requests positioning data via the GSM network and DS delivers network correction streams via the GSM DS network)(**paragraph 0060,0061,0062**).

Consider **claim 5**, and as applied to claim 2 above, Robbins discloses the method of receiving said request from said mobile position determination unit **115 (figure 1)**(**paragraph 0060**); establishing said cellular telephone connection with base station (i.e., if distributed via a GSM network using a GSM cellular telephone)(**paragraph 0060-0064**); and requesting a position fix of said designated location (i.e., The declared location can be provided from a GPS fix determined by the mobile unit 115 or can be supplied by user input) (**paragraph 0060**).

Consider **claim 6**, and as applied to **claim 1 above**, Robbins discloses the method of utilizing a global positioning systems (GPS) receiver to determine a position fix of said designated (i.e., the declared location can be provided from a GPS fix determined by the mobile unit 115 or can be supplied by user input ) (**paragraph 0060**).

Consider **claim 7**, and as applied to **claim 6 above**, Robbins discloses the method wherein said GPS receiver is disposed in said mobile position determination unit **120** (i.e., a fully integrated mobile receiver as described in **paragraph 0062-0065** and shown in **figures 1 and 18**) and wherein said method further comprises:

locating said mobile position determination unit **115** proximate to said base station ( i.e., a mobile unit has a functionality equivalent to having a reference station at the current location of the mobile unit or at the declared location near (proximate ) the mobile unit) (**paragraph 0060**).

Utilizing said mobile position determination unit to determine said position fix (**paragraph 0060**).

Consider **claim 8**, and as applied to **claim 6 above**, Robbins discloses the method wherein said base station comprises a real-time kinematics (RTK ) base station and wherein said method further comprises: communicatively coupling said radio transmitter with a cellular communications device (i.e., using the Trimble Navigation limited products disclosed by Robbins to obtain GPS corrections for RTK, you need your own base station that is no more than ten kilometers from the field you are working in. Trimble Navigation limited further states that for DGPS, you can use your own base station, a correction service provider, or make use of the free radio beacon broadcasts in many regions. Therefore in conjunction with a GSM network

system for cellular distribution Robbins clearly describes the method above) (**paragraph 0062-0067**).

Consider **claim 10** and as applied to **claim 1 above** Robbins clearly discloses a method wherein said transmitting (i.e., via the Distribution System DS **110**) comprises selecting a frequency from a group of frequency ranges consisting of 150 MHz – 170 MHz and 450 MHz – 470 MHz (i.e., VHF/ UHF support the data transfer rates needed 120 bits per second or better)(**paragraph 0058**).

Consider **claim 11** Robbins clearly show and disclose a system (**figure 1**) for delivering Virtual Reference Station (VRS) data comprising: a VRS control station **105** (**figure 1**) for creating a data message comprising pseudorange data derived for said designated location and pseudorange corrections for a designated region surrounding said designated location (**paragraph 0054**);

a base station located in said designated region surrounding said designated location, said base station for receiving said data message from said VRS control center **105** (**figure 1**) via a cellular telephone (i.e., GSM phone) (**paragraph 0058**) and for transmitting said data message using a radio transmitter ( i.e., it is well known that GSM networks are equipped with Base station transceiver BTS with a fundamental duty of receiving and transmitting. The distribution system 110 of figure 1 can comprise of delivery media to GSM telephones. GSM networks are well known in the art to consist of base stations, transmitters, etc.) (**paragraphs 0058 and 0064**); and a mobile positioning determination unit 115 (figure 1) for receiving said data message from said base station (**paragraphs 0054-0061**).

Consider **claim 12**, and as applied to **claim 11 above**, Robbins clearly show and disclose a system wherein said VRS control center derives the pseudorange data and pseudorange corrections in response to a request for the VRS data (i.e. The declared location of a mobile unit)(**paragraph 0060**).

Consider **claim 13**, and as applied to **claim 12 above**, Robbins discloses a system wherein said base station initiates said request(i.e. using a GSM mobile network as the distribution system it is clear that the request must traverse or originate in some way, shape or form involving a base station. It is well known that the basic functionality of a BTS is to receive and transmit)(**paragraph 0058 and 0064**).

Consider **claim 14**, and as applied to **claim 13 above**, Robbins discloses a system wherein said base station initiates said request in response to receiving a message (i.e., varying message types )(**paragraph 0094 and 0095**) from said mobile position determination unit **115** (**figure 1**) (i.e., an integrated GSM phone requests positioning data via the GSM network and DS delivers network correction streams via the GSM DS network)(**paragraph 0060,0061,0062**).

Consider **claim 15**, and as applied to **claim 12 above**, Robbins discloses a system wherein the VRS Control center **105** (**figure 1**) receiving said request from said mobile position determination unit **115** (**figure 1**)(**paragraph 0060**) and establishing said cellular telephone connection with base station (i.e., if distributed via a GSM network using a GSM cellular telephone)(**paragraph 0060-0064**); to request a position fix of said designated location (i.e., The declared location can be provided from a GPS fix determined by the mobile unit 115 or can be supplied by user input) (**paragraph 0060**).

Consider **claim 16**, and as applied to **claim 11 above**, Robbins discloses a system comprising a global positioning system (GPS) receiver to determine a position fix of said designated (i.e., the declared location can be provided from a GPS fix determined by the mobile unit 115 or can be supplied by user input) (paragraph 0060).

Consider **claim 17**, and as applied to **claim 16 above**, Robbins discloses a system wherein said GPS receiver is disposed in said mobile position determination unit **120** (i.e., a fully integrated mobile receiver as described in **paragraph 0062-0065** and shown in **figures 1 and 18**).

Consider **claim 18**, and as applied to **claim 16 above**, Robbins discloses a system wherein said base station comprises a real-time kinematics (RTK) base station and wherein said radio transmitter is communicatively coupled with a cellular device (i.e., using the Trimble Navigation limited products disclosed by Robbins to obtain GPS corrections for RTK, you need your own base station that is no more than ten kilometers from the field you are working in. Trimble Navigation limited further states that for DGPS, you can use your own base station, a correction service provider, or make use of the free radio beacon broadcasts in many regions. Therefore in conjunction with a GSM network system for cellular distribution Robbins clearly describes the method above) (paragraph 0062-0067).

Consider **claim 20** and as applied to **claim 11 above** Robbins clearly discloses a system wherein said radio transmitter (i.e., via the Distribution System **DS 110**) transmits said data message at a frequency selected from a group of frequency ranges consisting of 150 MHz – 170 MHz and 450 MHz - 470 MHz (i.e., VHF/ UHF support the data transfer rates needed 120 bits per second or better)(paragraph 0058)

Consider **claim 21** Robbins clearly show and disclose a method for delivering Virtual Reference Station data (VRS) data comprising: a plurality of reference stations **105** (i.e., RS1-RSN) (**abstract, paragraph 0049, and figure 1**) to derive pseudorange data for said designated location and pseudorange correction for a designated region surrounding said designated location (**paragraph 0054**); sending a data message comprising pseudorange data and pseudorange corrections to a base station via a cellular telephone network, and wherein said base station is located in said designated region surrounding said designated location(i.e., to obtain GPS corrections for RTK, you need your own base station that is no more than ten kilometers from the field you are working in )(**paragraphs 0058 and 0064**); and transmitting said data message from said base station to a mobile position determination unit located in said designated region surrounding said designated location using a radio transmitter(**paragraphs 0058 and 0064**)(i.e., the distribution system 110 of figure 1 can comprise of delivery media to GSM telephones. GSM networks are well known in the art to consist of base stations, transmitters, etc.)

Consider **claim 22**, and as applied to **claim 21 above**, Robbins clearly show and disclose a method wherein said VRS control center receives a request for said Virtual Reference Station data and further comprising: deriving the pseudorange data and pseudorange corrections in response to said request (i.e. The declared location of a mobile unit)(**paragraph 0060**).

Consider **claim 23**, and as applied to **claim 22 above**, Robbins discloses a method wherein receiving said request from said base station (i.e. using a GSM mobile network as the distribution system it is clear that the request must traverse or originate in some way, shape or form involving a base station. The basic functionality of a BTS is to receive and transmit)(**paragraph 0058 and 0064**).

Consider **claim 24**, and as applied to **claim 23 above**, Robbins discloses the method of initiating said request in response to receiving a message (i.e., varying message types )(paragraph 0094 and 0095) from said mobile position determination unit receiving said request from said mobile position determination unit **115 (figure 1)** (i.e., an integrated GSM phone requests positioning data via the GSM network and DS delivers network correction streams via the GSM DS network)(paragraph 0060,0061,0062).

Consider **claim 25**, and as applied to **claim 22 above**, Robbins discloses the method of receiving said request from said mobile position determination unit **115 (figure 1)**(paragraph 0060); establishing said cellular telephone connection with base station (i.e., if distributed via a GSM network using a GSM cellular telephone)(paragraph 0060-0064); and requesting a position fix of said designated location (i.e., The declared location can be provided from a GPS fix determined by the mobile unit 115 or can be supplied by user input) (paragraph 0060).

Consider **claim 26**, and as applied to **claim 21 above**, Robbins discloses the method of utilizing a global positioning systems (GPS) receiver to determine a position fix of said designated (i.e., the declared location can be provided from a GPS fix determined by the mobile unit 115 or can be supplied by user input ) (paragraph 0060).

Consider **claim 27**, and as applied to **claim 26 above**, Robbins discloses the method wherein said GPS receiver is disposed in said mobile position determination unit **120** (i.e., a fully integrated mobile receiver as described in paragraph 0062-0065 and shown in **figures 1 and 18**) and wherein said method further comprises:

locating said mobile position determination unit **115** proximate to said base station ( i.e., a mobile unit has a functionality equivalent to having a reference station at the current location of the mobile unit or at the declared location near (proximate ) the mobile unit) (**paragraph 0060**).

Utilizing said mobile position determination unit to determine said position fix (**paragraph 0060**).

Consider **claim 28, and as applied to claim 26 above**, Robbins discloses the method wherein said base station comprises a real-time kinematics (RTK ) base station and wherein said method further comprises: communicatively coupling said radio transmitter with a cellular communications device (i.e., using the Trimble Navigation limited products disclosed by Robbins to obtain GPS corrections for RTK, you need your own base station that is no more than ten kilometers from the field you are working in. Trimble Navigation limited further states that for DGPS, you can use your own base station, a correction service provider, or make use of the free radio beacon broadcasts in many regions. Therefore in conjunction with a GSM network system for cellular distribution Robbins clearly describes the method above) (**paragraph 0062-0067**).

Consider **claim 30 and as applied to claim 21 above** Robbins clearly discloses a method wherein said transmitting (i.e., via the Distribution System DS **110**) comprises selecting a frequency from a group of frequency ranges consisting of 150 MHz – 170 MHz and 450 MHz - 470 MHz (i.e., VHF/ UHF support the data transfer rates needed 120 bits per second or better)(**paragraph 0058**).

***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

**Claims 9,19, and 29** are rejected under 35 U.S.C. 103(a) as being unpatentable over **Robbins** (U.S. Patent Pub #2002/0198657 A1) in view of **Friedman** (W0 01/50151 A1).

Consider **claims 9,19, and 29** and as applied to **claims 8,18, and 28**. Robbins clearly disclose the claimed method and system however, Robbins does not clearly disclose the method and system wherein said radio transmitter comprises a bluetooth communications device.

In the same field of endeavor, Friedman discloses a radio transmitter **54**(**figure 6**) **75** (**figure 7**) comprises a Bluetooth communications device **70** (**figure 7**), and wherein said method further comprises sending a data message to said mobile position determination unit **50** (i.e., mobile DSP)(**figure 7**) using said Bluetooth communication device (**figure 7**).

Therefore it would have been obvious to a person of ordinary skill in the art at the time of the invention to include a bluetooth communication device in a transmitter as taught by Friedman

Art Unit: 2687

in the method and systems of Robbins for the purpose of improving location determination in areas that are not covered by other wireless means.

***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Charles Shedrick whose telephone number is (571)-272-8621. The examiner can normally be reached on Monday thru Friday 8:00AM-4:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Kincaid Lester can be reached on (571)-272-7922. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Charles Shedrick  
August 1, 2005  
AU 2687

*Charles P. Gutierrez*  
RAFAEL PEREZ-GUTIERREZ  
PATENT EXAMINER  
8/8/05